


AD 550

Doosan
Mecc Alte
D+ &



ISO8528	GC,) &
SZUTEST	GC - \$\$\$
CE	

2000/14/EC

&\$\$\$#(#

z) \$ z' z' D:

	"	kw	"	kw	Amp
400/230	550,00	440,00	500,00	400,00	722,00

fP GDE GC,) & fDF D% \$1 % %& GC " \$(** z& GC

Standard Specifications

z fi ! E z z

1

ALTERNATOR
D: A Z 5J F

TRANSFER SWITCH

AD 550

Doosan
Mecc Alte
D+' &'

Manufacturer		Doosan		
Model		P180LE		
		%\$\$' "# "		
		494,00 kw [662,50HP]		
	L	18,300		
	"	128 x 142		
		15,0:1		
	fl # ȷ	"# "	1500	
	fl ȷ	L	35,00	
		L	91,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	33,70		
	' # "	565,00		
	' # "	97,90		
	° C	580,00		
		24 V d.c.		
	Load	%\$\$i	'+) i) \$i
	# "	111,60	81,30	54,80

		Mecc Alte		
		ECO 40-3S/4		
	Hz	50		
	"	500,00		
7cg'		0,80		
		3		
	fl ȷ	400/230		
	A	722,00		
Temperature		H		

		fl ȷ		fl ȷ	
	"	"	"	"	L
AD 550	3600,00	3264,00	1550,00	1991,00	850,00
		fl ȷ		fl ȷ	
	"	"	"	"	L
MS 80	4790	4810	1606	2615	850

AD 550

Doosan
Mecc Alte
D+ &

f@z@Bl
f@z@Bl

"z" "z"

f@z@Bl

971

#

#

#

#

#

6G'9B'*\$-\$)

6G'9B'*\$\$\$!*!&

6G'9B'*\$\$\$!*!(

f&%) +L

f&)(, L

f&% \$L

GA 8

!&+""

)
&(\$)

ž

ž

ž

ž

%, !&*(

"

"

"

"

AD 550

Doosan
Mecc Alte
D+ & "



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

	"	1606
fl "L	"	4810
fl "L	"	2615
	L	850